


## Optical termination outlet (OTO), surface-mounted with pre-assembled cable



### Optical termination outlet (OTO), ready to splice with pre-assembled cable, 4x fibres, 15 m

· Scope of delivery: OTO, LC/APC coupling, connector and fibre optic cable

|  |  |
|--|--|
| <b>Article no:</b>                           | <b>4252028</b>   |
| EAN:   | 4013456579712  |
| Cable length                                 | 15 m   |
| Number of fibers                             | 4  |
| Cable routing                                | Bottom   |
| Certificate                                  | GHMT Channel Link (z7384b-22 ; c7384b-22)                      |
| Length                                       | 85 mm  |
| Width  | 85 mm  |
| Height                                       | 16 mm  |
| Network level                                | 4  |
| Installation type                            | Surface-mounted (on installation box) / multimedia distributor |
| Protection class                             | IP20   |
| Impact resistance                            | IK07   |
| Number of splice trays                       | 1  |
| Halogen-free                                 | Yes  |
| Loop length (splice tray)                    | 180  |
| Bending radius (splice tray)                 | 25 mm  |
| Splice protection holder                     | No   |
| Number of cable entries                      | 3  |
| Cabel entry Ø                                | 2,3 - 5,3 mm   |
| Temperature range storage                    | -10 °C / +60 °C  |
| Temperature range installation               | -10 °C / +60 °C  |
| Temperature range during operation           | -20 °C / +60 °C  |
| Colour                                       | Signal white (RAL 9003)  |
| Coupler   LC/APC Duplex                      | with flange, SC Simplex footprint                              |
| Coupler   Amount                             | 2  |
| Coupler   Sleeve material                    | Ceramic, slotted   |
| Coupler   Housing material                   | plastic, halogen-free, flame-retardant                         |
| Coupler   Laser and dust protection          | Integrated protection cap, blind plug                          |
| Coupler   Insertion Loss                     | ≤ 0,20 dB  |
| Coupler   Mating cycles                      | 1000   |
| Fibre optic line   Fibre optic class         | Single Mode OS2 (G.657.A2)                                     |
| Fibre optic line   LC/APC simplex connectors | 2x (Grade A)   |
| Fibre optic line   Fibre optic type          | Single Mode Optical Fibre                                      |
| Fibre optic line   Fibre optic color coding  | 1=red, 2=green, 3=blue, 4=yellow                               |
| Fibre optic line   Stranding element         | Aramid Garn  |
| Fibre optic line   Material                  | LSZH, IEC 60332-1  |
| Fibre optic line   ConstructionVo            | B2ca according to EN50575:2014 + A1:2016                       |
| Fibre optic line   Cable Ø                   | 2,4 mm +/- 0,25 mm   |
| Fibre optic line   Cable labeling            | KAISER GROUP FTTH Drop Cable 4E9/125 G657A2 CPR, B2ca          |
| Fibre optic line   Minimum bend radius       | 36 mm (Installation), 50 mm (Permanent)                        |

|   |  |
|---|--|
| Fibre optic line   Traction                           | 400 N (max. fibre load 0.50%), 200 N (max. fibre load 0.25%) |
| Fibre optic line   Compressive strength               | 200 N / 10 cm  |
| Fibre optic line   Temperature range storage          | -20 °C / +70 °C  |
| Fibre optic line   Temperature range installation     | -5 °C / +50 °C   |
| Fibre optic line   Temperature range during operation | -20 °C / +70 °C  |

The optical termination outlet will be the termination point of the optical fibre cable within the appartement / home. Due to the pre-assembled cable in 7 different cable lengths, this variant forms an optimal solution for structured cabling in network level 4.

- Compact fibre-optic subscriber connection
- Dimensions: 85x85x16 mm (LxWxH)
- Colour similar to RAL9003 signal white
- Ready to splice with pre-assembled cable in 7x lengths (10m, 15m, 20m, 25m, 30m, 50m and 70m) - other lengths available on request
- Available with 2 or 4 fibres
- High-quality fibre-optic cable G.657.A2 and BauPVo B2ca
- Retractable and blowable cable
- Handlicher Abrollkarton mit optimierter Installationshilfe

