

Spacer



Spacer

- for installation in insulated hollow ceilings
- retrofitting from below
- toolless mounting
- For \varnothing 68 – 80 mm installation openings
- height adjustable from 100 – 40 mm

Article no:	9310-10
EAN:	4013456551091
Depth	100 - 40 mm
installation from front, cut hole \varnothing	68 - 80 mm
max. installation depth for the LED luminaires	95 mm
max. ceiling exit (DA) \varnothing	80 mm
Cable entries max.	4
Dispatch	10

The spacer for the installation of swivelling built-in halogen and LED luminaires in various ceiling constructions. The housing ensures the necessary distance between the luminaire and the surrounding material. In this way, materials such as the moisture barrier and insulation are efficiently protected against the luminaire's high operating temperatures. This protective measure can be provided for both new buildings and retrofitting work. The housing is suitable for installation diameters between 68 and 80 mm, and can be adapted for use with different installation heights from 40 to 100 mm. After installation, the spacer stands securely on the boarding. This means that the installation diameter is fully retained and guarantees a secure fit.

- Installation in \varnothing 68 – 80 mm openings
- Maximum flexibility: Installation height from 100 – 40 mm
- Independent of boarding material and thickness
- Secure fit by means of installation on the ceiling
- Use with all standard LV / HV / LED lamps

