

On-site mixed concrete | Recoding to the new generation of HaloX®

The new generation of HaloX®

Previous product range




HaloX® 100
1281-00
Installation diameter $\leq \varnothing 100$ mm

Installation diameter
max. **$\varnothing 100$** mm



HaloX®-O*
1290-40
Installation diameter $\leq \varnothing 100$ mm



**HaloX® 100
with tunnel 190**
1281-30
Installation diameter $\leq \varnothing 100$ mm

Installation diameter
max. **$\varnothing 100$** mm
+ operating devices



**HaloX®-O*
with transformer tunnel**
1290-41
Installation diameter $\leq \varnothing 100$ mm



**HaloX®-O*
with short tunnel**
1290-42
Installation diameter $\leq \varnothing 100$ mm




HaloX® 180
1282-00
Installation diameter max. $\varnothing 180$ mm

Installation diameter
max. **$\varnothing 180$** mm




KompaX® 3*
1294-..
Installation diameter max. $\varnothing 215$ mm



**HaloX® 180
with tunnel 190**
1282-30
Installation diameter max. $\varnothing 180$ mm **HaloX® 180
with tunnel 325**
1282-40
Installation diameter max. $\varnothing 180$ mm

Installation diameter
max. **$\varnothing 180$** mm
+ operating devices



KompaX® 2
1292-..
Installation diameter max. $\varnothing 200$ mm




HaloX® 250
1283-00
Installation diameter max. $\varnothing 250$ mm

Installation diameter
max. **$\varnothing 250$** mm



KompaX® 3*
1294-..
Installation diameter max. $\varnothing 215$ mm



**HaloX® 250
with tunnel 325**
1283-40
Installation diameter max. $\varnothing 250$ mm

Installation diameter
max. **$\varnothing 250$** mm
+ Operating devices



KompaX® 2
1292-..
Installation diameter max. $\varnothing 200$ mm

KompaX® 1
1293-..
Installation diameter max. $\varnothing 300$ mm

* Discontinued items

KAISER GmbH & Co. KG

Ramsloh 4 · 58579 Schalksmühle
DEUTSCHLAND
Tel.+49 (0)2355/809-0 · Fax+49 (0)2355/809-21
www.kaiser-elektr.de · info@kaiser-elektr.de



System overview of HaloX®
www.kaiser-elektr.org/haloxytemoverviews



Prefabrication | Recoding to the new generation of HaloX®

The new generation of HaloX®


Previous product range



HaloX® 180
1282-71 / 1282-74

Installation diameter max. Ø 140 mm
(with tolerance compensation)
Installation diameter max. Ø 180 mm
(without tolerance compensation)

Installation diameter
max. Ø 180 mm



HaloX®-P*
1291-22

Installation diameter max. Ø 100 mm
(with tolerance compensation)
Installation diameter max. Ø 140 mm
(without tolerance compensation)



KompaX® 3*
1294-..

Installation diameter max. Ø 160 mm
(with tolerance compensation)
Installation diameter max. Ø 200 mm
(without tolerance compensation)



**HaloX® 180
with tunnel 190**
1282-72 / 1282-75


Installation diameter max. Ø 140 mm
(with tolerance compensation)
Installation diameter max. Ø 180 mm
(without tolerance compensation)



**HaloX® 180
with tunnel 325**
1282-73 / 1282-76

Installation diameter max. Ø 140 mm
(with tolerance compensation)
Installation diameter max. Ø 180 mm
(without tolerance compensation)

Installation diameter
max. Ø 180 mm
+ operating devices



HaloX®-P*
with transformer tunnel
1291-23

Installation diameter max. Ø 100 mm
(with tolerance compensation)
Installation diameter max. Ø 140 mm
(without tolerance compensation)



KompaX® 2
1292-..

Installation diameter max. Ø 140 mm
(with tolerance compensation)
Installation diameter max. Ø 180 mm
(without tolerance compensation)



HaloX® 250
1283-71 / 1283-74

Installation diameter max. Ø 210 mm
(with tolerance compensation)
Installation diameter max. Ø 250 mm
(without tolerance compensation)

Installation diameter
max. Ø 250 mm



KompaX® 3*
1294-..

Installation diameter max. Ø 160 mm
(with tolerance compensation)
Installation diameter max. Ø 200 mm
(without tolerance compensation)



**HaloX® 250
with tunnel 325**
1283-73 / 1283-76

Installation diameter max. Ø 210 mm
(with tolerance compensation)
Installation diameter max. Ø 250 mm
(without tolerance compensation)

Installation diameter
max. Ø 250 mm
+ operating devices



KompaX® 2
1292-..

Installation diameter max. Ø 140 mm
(with tolerance compensation)
Installation diameter max. Ø 180 mm
(without tolerance compensation)



KompaX® 1
1293-..

Installation diameter max. Ø 260 mm
(with tolerance compensation)
Installation diameter max. Ø 300 mm
(without tolerance compensation)

* Discontinued items

KAISER GmbH & Co. KG

Ramsloh 4 · 58579 Schalksmühle
DEUTSCHLAND
Tel.+49 (0)2355/809-0 · Fax +49 (0)2355/809-21
www.kaiser-elektra.de · info@kaiser-elektra.de



System overview of HaloX®

www.kaiser-elektra.org/haloxyssystemoverviews

 **KAI SER**
GROUP